U.S. Department of the Interior U.S. Geological Survey

Water-Chemistry and On-Site Sulfur-Speciation Data for Selected Springs in Yellowstone National Park, Wyoming, 1994-1995

Open-File Report 98-574



Water-Chemistry and On-Site Sulfur-Speciation Data for Selected Springs in Yellowstone National Park, Wyoming, 1994-1995

By James W. Ball¹, D. Kirk Nordstrom¹, Kirk M. Cunningham¹, Martin A. A. Schoonen², Yong Xu², and Jennifer M. DeMonge³

¹U.S. Geological Survey

²Department of Earth and Space Sciences, State University of New York at Stony Brook ³Department of Geology, University of Montana

Open-File Report 98-574



Boulder, Colorado 1998 Revised and reprinted, April 2001 U.S. DEPARTMENT OF THE INTERIOR BRUCE BABBITT, Secretary

U.S. GEOLOGICAL SURVEY Thomas J. Casadevall, Acting Director

The use of firm, trade, and brand names in this report is for identification purposes only and does not constitute endorsement by the U.S. Geological Survey.

For additional information write to:	Copies of this report can be purchased from:
Chief, Branch of Regional Research	U.S. Geological Survey
U.S. Geological Survey	Branch of Information Services
Denver Federal Center	Denver Federal Center,
Box 25046, MS-418	Box 25286
Denver, Colorado 80225	Denver, Colorado 80225-0286

CONTENTS

ABSTRACT	1
	 . 1
	 . 1
METHODS OF SAMPLE COLLECTION, STABILIZATION, AND ANALYSIS	 . 4
Sample Collection	 . 4
Analytical Methods	 10
Sample Treatment for Thiosulfate and Sulfate Determinations	 10
WATER-CHEMISTRY DATA	 12
SULFUR-SPECIATION DATA	 12
REFERENCES CITED	 26
APPENDIX	 29

FIGURES

1. Map showing locations of sampled springs in Yellowstone National Park, Wyo	3
2-5. Schematic maps showing:	
2. Sampling sites for Ojo Caliente Spring and its overflow channel,	
Lower Geyser Basin, 1994	5
3. Sampling sites for Frying Pan Spring and its overflow channel, Norris	
Geyser Basin, 1994	6
4. Sampling sites for Angel Terrace Spring and its overflow channel,	
Mammoth Hot Springs complex, 1994	7
5. Sampling sites for Azure Spring and its overflow channel, Lower	
Geyser Basin, 1995	8
-	

TABLES

1.	Storage and stabilization methods for filtered samples	9
2.	Reactions of reduced sulfur species	11
3.	Site data and water analyses for Ojo Caliente Spring and its overflow channel, Lower	
	Geyser Basin	14
4.	Site data and water analyses for Frying Pan Spring and its overflow channel, Norris	
	Geyser Basin	17
5.	Site data and water analyses for Angel Terrace Spring and its overflow channel,	
	Mammoth Hot Springs complex	19
6.	Site data and water analyses for Azure Spring and its overflow channel, Lower Geyser	
	Basin	20
7.	Site data and water analyses for miscellaneous springs	22
8.	² H and ¹⁸ O isotope analyses	24
9.	Comparison of historic data on sulfur species concentrations for selected locations	25
10	. Methods of analysis	30
11	. Explanation of methods of analysis	31
12	. Measurements of Standard Reference Waters	35

CONVERSION FACTORS AND ABBREVIATIONS

To obtain gal (gallon) oz (ounce)
gal (gallon)
oz (ounce)
OZ (Ounce)
ft (foot)
verted to degrees Fahrenheit (°F) as follows: $< ^{\circ}C + 32$
abbreviations
EC (electro-chemical method)
FAAS (flame atomic absorption
spectrometry)
FIAS (flow injection analysis system)
IC (ion chromatography)
ICP (inductively-coupled plasma atomic
emission spectrometry)
ISOT (stable isotope analysis)
MHZ (megahertz)
PTFE (polytetrafluoroethylene)
RF (radio frequency)
SLAP (Standard Light Antarctic
Precipitation)
Spec. cond. (specific conductance)
SRWS (standard reference water sample)
TITR (titrimetry)
UV (ultraviolet)
VSMOW (Vienna Standard Mean Ocean
Water)
YNP (Yellowstone National Park)
ZGFAAS (Zeeman-corrected graphite
furnace atomic absorption
spectrometry)
· · · ·

Water-Chemistry and On-Site Sulfur-Speciation Data for Selected Springs in Yellowstone National Park, Wyoming, 1994-1995

By James W. Ball, D. Kirk Nordstrom, Kirk M. Cunningham, Martin A. A. Schoonen, Yong Xu, and Jennifer M. DeMonge

ABSTRACT

Forty-two water analyses are reported for samples collected at 8 hot springs and their overflow drainages, two geysers, and two ambient-temperature acid streams in Yellowstone National Park during 1994-95. These water samples were collected and analyzed as part of the initial research investigations on sulfur redox speciation in the hot springs of Yellowstone and to document chemical changes in overflows that affect major ions, redox species, and trace elements. The sulfur redox speciation research is a collaboration between the State University of New York (SUNY) at Stony Brook and the U.S. Geological Survey (USGS). Four hot springs, Ojo Caliente, Azure, Frying Pan, and Angel Terrace, were studied in detail. Analyses were performed adjacent to the sampling site or in an on-site mobile lab truck constructed by the USGS, or later in a USGS laboratory.

Water temperature, specific conductance, pH, Eh, D.O., and dissolved H₂S were determined adjacent to the sample source at the time of sampling. Alkalinity and F⁻ were determined on-site on the day of sample collection. Thiosulfate and polythionates were determined as soon as possible (minutes to hours later) by ion chromatography (IC). Other major anions (Cl⁻, SO₄²⁻, Br⁻) also were determined on-site by IC within two days of sample collection. Ammonium, Fe(II), and Fe(total) were determined on-site by ultraviolet/visible spectrophotometry within two days of sample collection. Later in the USGS laboratory, densities were determined. Concentrations of Ca, Mg, Li, Na, and K were determined by flame atomic absorption and emission (Na, K) spectrometry. Concentrations of Al, As, B, Ba, Be, Ca, Cd, Co, Cr, Cu, Fe(total), K, Mg, Mn, Na, Ni, Pb, Si, Sr, V, and Zn were determined by inductively-coupled plasma optical emission spectrometry. Trace concentrations of Al and Mg were determined by Zeeman-corrected graphite furnace atomic absorption spectrometry.

Three important conclusions from the sampling and analyses are: (1) variability in H_2S concentrations can be caused as much by sampling and preservation artifacts as by actual variations in water composition over time, (2) historical determinations of $S_2O_3^{2-}$ were subject to overestimation, most likely because of inadequate preservation leading to H_2S oxidation, and (3) $S_2O_3^{2-}$ is a common constituent of hot spring waters.

INTRODUCTION

Spectacular hot spring and geyser activity led to the designation of Yellowstone National Park (YNP) as the first national park in the world and inspired numerous scientific investigations. Investigations into the water chemistry of hot springs, geysers, streams, and rivers have been accomplished primarily by the USGS, dating back to the report of Gooch and Whitfield (1888) and the comprehensive study by Allen and Day (1935). More recent water-chemistry data are available for 6 samples reported by White and others (1963), 166 samples reported by Rowe and others

(1973), 541 samples reported by Thompson and others (1975), 422 samples reported by Thompson and Yadav (1979), 45 samples reported by Stauffer and others (1980), 38 samples reported by Thompson and Hutchinson (1981), 17 samples reported by Kharaka and others (1991), and over 450 samples reported by Thompson and DeMonge (1996). Additional data are reported by White and others (1988), Fournier (1989), Fournier and others (1994), and Ball and others (1998).

Waters at YNP have a wide range of compositions. The pH values range from 1 to 10, temperatures range from ambient to boiling, and there are high concentrations of As, H_2S , SO_4^{2-} , and HCO_3^{-} . Numerous redox reactions and mineral-precipitation reactions occur. As well as being valuable natural resources, active geothermal areas such as YNP provide enormous insight into formation of mineral deposits, microbiological processes in extreme environments, and water-rock interactions.

The present study is the first phase of collaborative research between the USGS, SUNY at Stony Brook, and Northern Arizona University. The purpose of this investigation is to study the occurrence, origin, rates of formation and disappearance, and hydrogeochemical significance of unstable redox species of sulfur in mineral springs and geothermal waters.

Forty-two water samples were collected and analyzed for major and trace constituents from five areas (fig. 1): Mammoth Hot Springs (Angel Terrace), Norris Geyser Basin (including Frying Pan Spring), Lower Geyser Basin (Ojo Caliente and Azure Spring), Washburn Hot Springs, and Brimstone Basin. Hot springs with well-defined overflow channels were sampled in detail, especially those at Angel Terrace, Frying Pan Spring, Ojo Caliente, and Azure Spring. Water discharging from these springs provided a range of pH values and dissolved constituent concentrations. Discharge from each spring flowed into a small, well-defined channel, facilitating collection of samples and permitting study of chemical reactions during downstream transport. These analyses for the five hot-spring areas may be some of the most complete available, containing major ions, trace elements, and some redox species such as Fe(II)/Fe(total), H_2S , $S_2O_3^{2-}$, and SO_4^{2-} .

The authors thank the following USGS personnel: G. R. Aiken for dissolved organic carbon analyses, R. C. Antweiler and B. Kumler for ammonium analyses, and T. B. Coplen, J. A. Hopple, and C. Kendall for isotope determinations. We acknowledge the contributions of Cherie Ball in preparing publication versions of the figures for this report. The participation of SUNY at Stony Brook in this project is sponsored by the National Science Foundation-Earth Sciences.

We extend our appreciation to the staff of Yellowstone National Park for permission to collect water samples. We are especially thankful to the late Rick Hutchinson for his advice and his interest in our work since 1974. We thank Bob Lindstrom for arranging transportation and accompanying us to Brimstone Basin. We also thank Mike Thompson, formerly of the USGS, for leading us through Norris and Lower Geyser Basins.



Figure 1. Locations of sampled springs in Yellowstone National Park, Wyo.

METHODS OF SAMPLE COLLECTION, STABILIZATION, AND ANALYSIS

Many analyses were performed on each sample. Physical properties determined included temperature, pH, specific conductance, and density. Concentrations of D.O., H_2S , NH_4^+ , SiO_2 , major cations, trace metals, Fe(II), Fe(total), major anions, alkalinity, $S_2O_3^{2-}$, and DOC, as well as stable isotopes of H and O, were determined.

Sample Collection

Samples were collected as close to the source of each spring as possible and at various locations along the downstream overflow channel, as illustrated schematically in figs. 2-5 for Ojo Caliente Spring, Frying Pan Spring, Angel Terrace Spring, and Azure Spring, respectively. For safety, to protect fragile hot spring mineral formations, and to minimize changes in temperature, pH, and water chemistry during sampling, samples from the middle of pools were taken using an insulated stainless steel container attached to the end of an extendable aluminum pole. The container was rinsed several times with sample water to assure thermal equilibration and to minimize sample contamination. At more easily accessible sites, spring water was withdrawn directly from the source or channel.



Figure 2. Sampling sites for Ojo Caliente Spring and its overflow channel, Lower Geyser Basin, 1994.



Figure 3. Sampling sites for Frying Pan Spring and its overflow channel, Norris Geyser Basin, 1994.



Figure 4. Sampling sites for Angel Terrace Spring and its overflow channel, Mammoth Hot Springs complex, 1994.



Figure 5. Sampling sites for Azure Spring and its overflow channel, Lower Geyser Basin, 1995.

At all sites, samples for the following determinations were filtered upon withdrawal from the source: major cations, trace metals, Fe(II) and Fe(total), major anions, alkalinity, density, DOC, NH₄⁺, dissolved SiO₂, H₂S, SO₄²⁻, S₂O₃²⁻, and isotopes of H and O. Samples for H₂S, SO₄²⁻, and S₂O₃²⁻ analyses were suctioned by hand into a plastic syringe to avoid the formation of head space, then pressure-filtered through syringe-mounted 0.45-µm membrane filters; stabilizing reagents were put into the syringe before the sample was drawn into it. All other samples were pumped from the spring with a portable peristaltic pump through medical-grade silicone tubing, then through a 142-mm diameter all-plastic filter holder (Kennedy and others, 1976) containing a 0.45-µm Millipore filter membrane, except for samples 94WA110 and 95WA116 where a 0.1-µm filter membrane was used. Storage and stabilization of filtered samples are summarized in table 1.

Unfiltered samples were used for analyses of pH, Eh, D.O., temperature, and specific conductance. Temperature, specific conductance, and D.O. measurements were made by immersing probes directly into the source or into a sample collected in the insulated container. Measurements for Eh and pH were made on unfiltered sample water pumped from the spring through an acrylic plastic flow-through cell containing a thermometer, Eh and pH electrodes, and test tubes containing calibrating solutions.

Sample type(s)	Storage container	Stabilization treatment in addition to refrigeration
Major cations, trace metals, Fe(II), and Fe(total)	Polyethylene or PTFE bottles, soaked in 10% HNO ₃ and rinsed with double- distilled water	1% (v/v) redistilled 6 N HCl added
Major anions, alkalinity, and density	Polyethylene bottles, rinsed in 10% HNO ₃ and soaked in double-distilled water aliquots for >48 hours	None
DOC	Baked (450°C) amber glass bottles with PTFE-lined caps	None
$\mathrm{NH_4}^+$	Same as major cations, trace metals, Fe(II), and Fe(total)	1% (v/v) 1:10 redistilled H ₂ SO ₄ added
Dissolved SiO ₂	Same as major anions, alkalinity, and density	Diluted 1:10 immediately with distilled H ₂ O
SO ₄ ²⁻ , S ₂ O ₃ ²⁻	60 mL plastic syringe	1.6% (v/v) 1 M Cd-(OOC- CH ₃) ₂ , CdCl ₂ , or ZnCl ₂ plus 0.2% (v/v) 5 M NaOH added to precipitate S(-II)

Table 1. Storage and stabilization methods for filtered samples

Analytical Methods

The analytical methods are summarized in the Appendix at the back of the report (tables 10 and 11). Because most determinations were accomplished using established procedures, the method corresponding to each descriptor in table 10 is described briefly in table 11. In the following paragraphs, only general conditions or variants of standard procedures are discussed.

All reagents were of purity at least equal to the reagent-grade standards of the American Chemical Society. Doubly-distilled de-ionized water and re-distilled acids were used in all preparations. For inductively-coupled plasma, flame atomic-absorption, and graphite-furnace atomic-absorption spectrometric analyses, external standards, blanks, sample dilutions, and spiking solutions were made with commercial ICP elemental standard solutions or standard solutions composed of elements or their compounds of the highest commercially-available purity. USGS standard reference water samples (SRWS) were used as independent standards.

Samples were diluted as necessary to bring the analyte concentration within the optimal range of the method. For elemental analyses, several dilutions of each sample, with the extremes of the range differing by dilution factors of 2 to 10, were analyzed to check for concentration effects on the analytical method.

Calibration curves were determined by using standards within each set of analyses. If matrix effects were evident, spike-recovery and/or standard-addition measurements were performed. USGS SRWS T-117, T-115, and T-111 were used to check the analytical methods for major and trace metals, and SRWS M-102 was used to check the analytical methods for major anions. The SRWS data are presented in table 12 in the Appendix. Estimates of ICP detection limits are reported in table 11 in the Appendix and were assumed equal to $3\sigma_{blank}$, where σ_{blank} is the standard deviation of several dozen measurements of the constituent in a blank solution treated as a sample. Also listed in table 11 are typical values of analytical reproducibility for each method of analysis in samples containing the analyte at concentrations at least ten times the detection limit. These parameters were estimated for FAAS and ZGFAAS in a similar manner, but using only about a dozen measurements of blanks.

Sample Treatment for Thiosulfate and Sulfate Determinations

Determination of dissolved sulfur species presents particularly difficult analytical challenges, making the evaluation of sampling and analytical procedures critical to the success of the research. Hence, methods of collection and analysis are reported. For example, dissolved H₂S can volatilize rapidly or oxidize to S, $S_2O_3^{2^-}$, other S species of intermediate oxidation state, and $SO_4^{2^-}$. Without proper precautions, all these species can be considered unstable and subject to change. Because on-site determinations or special preservation techniques are crucial for reliable determination of unstable species concentrations, a USGS mobile lab truck with an on-board ion chromatograph, autotitrator, and UV-visible spectrophotometer was used to determine unstable species concentrations within minutes to hours of sample collection.

The distribution of sulfur species during oxidation of H_2S will change with storage time according to the rates of several competing reactions. These reactions, based on the works of Chen and Morris (1972), O'Brien and Birkner (1977), and Zhang and Millero (1994) are listed in table 2.

Table 2. Reactions	of reduced	sulfur	species
--------------------	------------	--------	---------

Reaction	Conditions where reaction rate is at a maximum
$HS^- + H^+ \leftrightarrow H_2S \rightarrow H_2S \uparrow$	$pH \le 6$
$HS^- + 2O_2 \rightarrow SO_4^{2-} + H^+$	$6 \le pH \le 8.5$, $[HS^-]:[O_2]$ low
$2HS^- + 2O_2 \rightarrow S_2O_3^{-2-} + H_2O$	$pH \ge 6$, $[HS^-]:[O_2]$ low
$HS^- + {}^3/_2O_2 \rightarrow SO_3{}^{2-} + H^+$	$pH \ge 7$, $[HS^-]:[O_2]$ low
$HS^- + \frac{1}{2}O_2 + H^+ \longrightarrow S + H_2O$	$6 \le pH \le 8.5$, [HS ⁻]:[O ₂] high
$S_n + HS^- \leftrightarrow S_{n+1}^{2-} + H^+ \ (n = 4,5)$	$6 \le pH \le 8$, [HS ⁻]:[O ₂] high
$S_n^{2-} + {}^3/_2O_2 \rightarrow SO_3^{2-} + (n-1)S$	$6 \le pH \le 8$, [HS ⁻]:[O ₂] high
$S_n^{2-} + 2O_2 + 2H^+ \rightarrow S_2O_3^{2-} + H_2O + (n-2)S$	$6 \le pH \le 8$, [HS ⁻]:[O ₂] high
$\mathrm{SO_3}^{2-} + \frac{1}{2}\mathrm{O_2} \rightarrow \mathrm{SO_4}^{2-}$	All pH
$S + SO_3^{2-} \leftrightarrow S_2O_3^{2-}$	$7 \leq pH \leq 8$
$S_2O_3^{2-} + {}^5/_2O_2 \rightarrow 2SO_4^{2-}$	Temperature $\geq 100^{\circ}$ C

In the hot springs, high temperature and the presence of oxidation-catalyzing bacteria cause these reactions to proceed at a much faster rate than in cooled and filtered samples stored for later analysis. For example, $S_2O_3^{2-}$ is oxidized rapidly to SO_4^{2-} at high temperatures, but this reaction proceeds at a negligible rate (Rolla and Chakrabarti, 1982) under typical sample-storage conditions. However, at the neutral pH and high initial [HS⁻]:[O₂] ratio of Ojo Caliente Spring, Azure Spring, and Angel Terrace Spring waters, the oxidation reactions of S(-II) occur with a half-life comparable to that of the storage time between sample collection and analysis. In these types of samples, major oxidation products are expected to be SO_4^{2-} and $S_2O_3^{2-}$, with elemental S, SO_3^{2-} , polythionates ($S_nO_6^{2-}$), and polysulfides (S_n^{2-}) as minor products.

To prevent over-estimation of the *in-situ* concentration of SO_4^{2-} and $S_2O_3^{2-}$, S(-II) oxidation was minimized by drawing unfiltered sample into a 60 mL syringe containing either 1 mL of 1 M Cd-(OOC-CH₃)₂ (1994 sampling) or I mL of 1 M ZnCl₂ (1995 sampling), plus 0.5 mL 5 M NaOH. This technique caused the oxidation-resistant ZnS or CdS species to precipitate. The sample was then pressure-filtered directly into the ion chromatograph on-site in the mobile laboratory or was stored on ice and analyzed a few days to weeks later at the USGS laboratory in Boulder, Colorado, or SUNY at Stony Brook. The H₂S concentrations range from <0.005 to 8 mg/L. For samples having H₂S concentrations toward the higher end of this range, $S_2O_3^{2-}$ concentrations were higher in the stored sample splits than in those analyzed on-site. For samples containing H₂S concentrations toward the lower end of the range, $S_2O_3^{2-}$ concentrations were lower in the stored sample splits than in those analyzed on-site. This result suggests that preservation using CdCl₂ or ZnCl₂ does not prevent oxidation of either S(-II) to $S_2O_3^{2-}$ or $S_2O_3^{2-}$ to SO_4^{2-} upon longer term storage. Cd initially appeared to be the superior precipitating agent because the smaller solubility product constant of CdS (K = $10^{-27.0}$) compared with the solubility product constant for ZnS (K = $10^{-22.5}$) (Smith and Martell, 1976) should result in better preservation of the S(-II). However, recent work (Xu and Schoonen, 1995; Xu and others, 1996) has established that semiconductors such as pyrite (FeS₂) and CdS can catalyze the oxidation of $S_2O_3^{-2}$ by O_2 . The catalytic effect depends on the energy position of the conduction and valence bands of the semiconductor relative to the standard potential of the $S_2O_3^{2-}/SO_4^{2-}$ redox couple in solution. By contrast, the conduction and valence band energies of ZnS cannot facilitate the $S_2O_3^{2-}$ oxidation reaction.

Based on the observations and discussions above, $S_2O_3^{2-}$ in water samples needs to be stabilized by adding 1 mL of 1 M ZnCl₂ and 0.5 mL of 5 M NaOH to 60 mL of sample, storing the sample on ice, and analyzing it as quickly as possible, preferably within 2 days.

WATER-CHEMISTRY DATA

Site data and water analyses for YNP springs sampled in 1994 and 1995 are presented in tables 3-7. The results of ²H and ¹⁸O isotope analyses are listed in table 8. Methods used in these analyses are listed in table 11 in the Appendix. Samples are sorted by spring, then by date of sample collection, and then by sampling site along the downstream overflow channel (if present). In these tables, "source" samples were collected at the origin of the spring, and "overflow channel" samples were collected at various distances downstream from the source. For data sets that contained alkalinity and concentrations of major anions and major cations, the WATEQ4F program (Ball and Nordstrom, 1991) was used to calculate ion sums and charge imbalance (C.I.), using the following calculation:

C.I. (percent) =
$$\frac{100 \times (\text{meq cations - meq anions})}{(\text{meq cations + meq anions}) \div 2}$$

Note that the result of this calculation is twice the value that would be reported by an analytical laboratory, because equation (1) relates the cation-anion difference to the average of the two rather than to the sum of the ions comprising them. Those data sets having charge imbalances exceeding 10 percent are footnoted if an explanation for the problem could be determined.

SULFUR-SPECIATION DATA

Sulfur-species data from historical reports and this study are compared in table 9 for six locations: Ojo Caliente, Azure, Frying Pan, and Angel Terrace springs, Echinus Geyser, and Cinder Pool. Chloride concentrations are included so that the consistency of the analysis can be checked and changes in concentration resulting from mixing of different subsurface waters can be ruled out. Two important points are made with these data. The first point is that H₂S concentrations can be highly variable. This variability may be caused as much by sampling and preservation artifacts as by actual variations in water chemistry over time. The second point is that while early analyses of $S_2O_3^{2-}$ such as those by Allen and Day (1935) were carefully done, they were subject to overestimation. The accepted method of that time, used by Allen and Day (1935), consisted of capturing the sample in a glass bottle, adding CdCO₃, and letting the sample stand overnight to react and remove dissolved H₂S. It is now known that excess $S_2O_3^{2-}$ is likely to form by oxidation of HS⁻,

and determination of the remaining $S_2O_3^{2-}$ by titration with starch iodine solution suffered from uncertainties. Allen and Day (1935) did not attempt to determine $S_2O_3^{2-}$ in acid springs such as Frying Pan because it was well known that $S_2O_3^{2-}$ is unstable in acid solutions. However, the oxidation rate for $S_2O_3^{2-}$ is much slower than that for H_2S so that $S_2O_3^{2-}$ can be found in these springs where a constant supply of hydrogen sulfide is provided. Ignoring Frying Pan Spring, which is poorly-defined in terms of input sources of water and gases, and ignoring Echinus Geyser because it occurs primarily as a geyser and thus always exhibits transient flow conditions, the remaining data show remarkable consistency in concentrations of sulfur species over long periods of time.

Two publications (Xu and others, 1998; 2000) discuss the origin of $S_2O_3^{2-}$ in hot spring waters and the formation and decomposition of $S_2O_3^{2-}$ and $S_nO_6^{2-}$ in Cinder Pool, Norris Geyser Basin. Data that form the basis of the discussions and conclusions in those reports are in tables 3-9.

Sample code number	94WA100	94WA101	94WA102	94WA103
Date collected	6/28/94	6/28/94	6/28/94	6/28/94
Flow channel distance (m)	0 (source)	0 (pool)	5.5	11
Temperature (°C)	93	91.9	88.5	85.8
Density (g/mL) at 20°C	0.99936	0.99929	0.99906	0.99916
pH (field/lab)	7.72/8.61	7.6/8.65	7.69/8.69	7.79/8.61
Spec. cond. (µS/cm) (field/lab)	1517/1595	1517/1596	1517/1614	1526/1614
Eh (V)	-0.156	-0.086	0.029	0.090
D.O. (mg/L)	0.1	0.5	0.75	1.1
Constituent (mg/L)				
Ca	1.00	0.91	0.88	0.91
Mg	0.001	0.0006	0.001	0.0007
Na	331	331	331	332
Κ	9.45	9.5	9.7	9.58
SO ₄	20.7	21.0	20.9	21.2
S_2O_3	0.269	0.275	0.351	0.477
H ₂ S	1.09	1.06	0.74	0.55
Alkalinity (as HCO ₃)	231.7	234.2	236.4	233.3
F	31.6	30.9	31.5	31.4
Cl	324	326	328	330
Br	1 15	1 17	1 17	1 18
SiO	243	236	248	248
NO ₂	¹ 0 132	0.032	0.032	<0.031
NH.	0.089	0.032	0.032	0.033
A1	0.009	0.020	0.03	0.033
Fe(tot)	0.0232	0.0273	0.014	0.0118
Fe(II)	0.0232	0.0237	0.014	0.0118
B	3.98	3.89	3 97	3 98
Li	3.96	3.09	3.98	4 01
Sr	0.008	0.007	0.006	0.006
Ba	0.000	<0.007	0.000	<0.000
Da Mn	<0.04	<0.04	<0.04	<0.04
Zn	<0.12	<0.12	<0.12	<0.12
Ph	<0.01	<0.01	<0.01	<0.01
Be	<0.13	<0.13	<0.13	<0.13
V	<0.001	<0.001	<0.001	<0.001
v Cr	<0.02	<0.02	<0.02	<0.02
	<0.03	<0.09	<0.03	<0.03
CO Ni	< 0.04	<0.04	< 0.04	< 0.04
	< 0.04	<0.04	< 0.04	< 0.04
Cu	< 0.14	<0.14	< 0.14	< 0.14
	< 0.04	< 0.04	< 0.04	< 0.04
AS(10121)	0.80	1.1	0.99	1.2/
DUC (mg/L)	1.0	0.8	0.6	0.4
Sum cations (meq/L)	14.6	15.2	15.2	15.3
Sum anions (meq/L)	14.9	15.0	15.0	15.3
Charge imbalance (percent)	-1.8	1.7	1.3	0.02

Table 3. Site data and water analyses for Ojo Caliente Spring and its overflow channel, Lower Geyser Basin

¹Likely to be contaminated.

Sample code number	94WA104	94WA105	94WA106	94WA107
Date collected	6/28/94	6/28/94	6/28/94	6/28/94
Flow channel distance (m)	14.9	14.9	17.7	26.2
Temperature (°C)	82.8	78.8	79.1	73.8
Density (g/mL) at 20°C	0.99903	0.99912	0.99935	0.99906
pH (field/lab)	7.86/8.66	7.94/8.70	7.92/8.72	8.12/8.71
Spec. cond. (uS/cm) (field/lab)	1542/1623	1568/1631	1556/1628	1580/1646
Eh (V)	0.142	0.183	0.148	0.171
D.O. (mg/L)	1.15	1.5	1.7	2.7
Constituent (mg/L)				
Ca	0.84	0.83	0.93	0.97
Mg	0.0004	0.0005	0.0003	0.0004
Na	336	325	339	340
Κ	9.67	9.74	9.66	9.84
SO_4	21.1	21.7	21.8	22.2
S_2O_3	0.574	0.756	0.702	0.629
H ₂ S	0.33	0.17	0.16	0.12
Alkalinity (as HCO_3)	237.6	240.1	245.2	233.9
F	31.6	32.0	31.9	32.7
Cl	331	331	332	335
Br	1.19	1.21	1.21	1.23
SiO ₂	257	260	262	259
NO ₃	< 0.031	< 0.031	< 0.031	< 0.031
NH ₄	0.031	0.014	0.013	0.008
Al	0.277	0.290	0.290	0.280
Fe(tot)	0.0021	< 0.0005	0.004	< 0.0005
Fe(II)	0.0021	< 0.0005	0.004	< 0.0005
В	3.98	4.02	4.16	4.01
Li	4.02	4.07	4.02	4.09
Sr	0.005	0.005	0.005	0.006
Ва	< 0.04	< 0.04	< 0.04	< 0.04
Mn	< 0.12	< 0.12	< 0.12	< 0.12
Zn	< 0.01	< 0.01	< 0.01	< 0.01
Pb	< 0.15	< 0.15	< 0.15	< 0.15
Be	< 0.001	< 0.001	< 0.001	< 0.001
V	< 0.02	< 0.02	< 0.02	< 0.02
Cr	< 0.09	< 0.09	< 0.09	< 0.09
Со	< 0.04	< 0.04	< 0.04	< 0.04
Ni	< 0.04	< 0.04	< 0.04	< 0.04
Cu	< 0.14	< 0.14	< 0.14	< 0.14
Cd	< 0.04	< 0.04	< 0.04	< 0.04
As(total)	1.5	1.53	1.29	1.48
DOC (mg/L)	0.4	0.3	0.4	0.3
Sum cations (meq/L)	15.4	15.5	15.6	15.6
Sum anions (meq/L)	15.2	15.3	15.4	15.3
Charge imbalance (percent)	1.5	1.5	1.0	1.8

Table 3. Site data and water analyses for Ojo Caliente Spring and its overflow channel, Lower Geyser Basin--continued

Sample code number	94WA108	94WA109	94WA110	94WA111	94WA112
Date collected	6/29/94	6/29/94	6/29/94	6/29/94	6/29/94
Flow channel distance (m)	13.4	16.8	20.4	25.3	29.9
Temperature (°C)	78	71.2	66.6	55	50.5
Density (g/mL) at 20°C	0.99906	0.99905	0.99935	0.99935	0.99927
pH (field/lab)	8.06/8.55	8.13/8.65	8.21/8.73	8.37/8.76	8.47/8.81
Spec. cond. (uS/cm) (field/lab)	1580/1626	1595/1640	1628/1647	1650/1687	1683/1710
Eh (V)	0.093	0.146	0.195	0.217	0.234
D.O. (mg/L)	2	2.3	2.7	3.3	3.7
Constituent (mg/L)					
Ca	0.95	0.94	1.01	1.00	1.01
Mg	0.0004	0.0007	¹ 0.010	0.0011	0.0003
Na	336	338	342	353	353
Κ	9.8	9.8	9.9	10.1	10.3
SO_4	21.6	22.5	22.5	23.2	23.7
S_2O_3	0.718	0.594	0.589	0.562	0.550
H ₂ S	0.17	0.09	0.06	0.03	0.03
Alkalinity (as HCO ₃)	241.4	241.8	244.1	249	251.4
F	32.5	32.8	33.1	34.0	34.3
Cl	332	334	335	343	345
Br	1.23	1.23	1.24	1.28	1.29
SiO ₂	257	253	257	263	263
NO ₃	< 0.031	< 0.031	< 0.031	< 0.031	< 0.031
NH4	0.013	0.009	0.013	< 0.006	< 0.006
Al	0.300	0.296	0.278	0.275	0.288
Fe(tot)	< 0.0005	< 0.0005	0.0007	< 0.0005	< 0.0005
Fe(II)	< 0.0005	< 0.0005	0.0007	< 0.0005	< 0.0005
В	4.02	3.97	4.02	4.15	4.16
Li	4.07	4.11	4.13	4.25	4.25
Sr	0.006	0.006	0.006	0.007	0.007
Ba	< 0.04	< 0.04	< 0.04	< 0.04	< 0.04
Mn	< 0.12	< 0.12	< 0.12	< 0.12	< 0.12
Zn	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
Pb	< 0.15	< 0.15	< 0.15	< 0.15	< 0.15
Be	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001
V	< 0.02	< 0.02	< 0.02	< 0.02	< 0.02
Cr	< 0.09	< 0.09	< 0.09	< 0.09	< 0.09
Со	< 0.04	< 0.04	< 0.04	< 0.04	< 0.04
Ni	< 0.04	< 0.04	< 0.04	< 0.04	< 0.04
Cu	< 0.14	< 0.14	< 0.14	< 0.14	< 0.14
Cd	< 0.04	< 0.04	< 0.04	< 0.04	< 0.04
As(total)	1.44	1.53	1.44	1.43	1.5
DOC (mg/L)	0.3	0.3	¹ 1.1	0.4	0.3
Sum cations (meq/L)	15.4	15.5	15.7	16.2	16.2
Sum anions (meq/L)	15.3	15.4	15.5	15.9	16.0
Charge imbalance (percent)	0.7	0.5	1.2	2.1	1.2

Table 3. Site data and water analyses for Ojo Caliente Spring and its overflow channel, Lower Geyser Basin--continued

¹Likely to be contaminated.

Sample code number	94WA113	94WA114	94WA115	94WA116
Date collected	6/29/94	6/29/94	6/29/94	6/29/94
Flow channel distance (m)	0 (source)	0 (outflow)	4.6	9.4
Temperature (°C)	78.2	58.1	52	48.5
Density (g/mL) at 20°C	0.99889	0.99895	0.9988	0.99893
pH (field/lab)	2.34/2.42	2.3/2.40	2.32/2.39	2.33/2.40
Spec. cond. (µS/cm) (field/lab)	1230/2070	1575/2260	1675/2150	1760/2190
Eh (V)	0.182	0.294	0.327	0.358
D.O. (mg/L)	2.4	2	2.5	2.65
Constituent (mg/L)				
Ca	2.41	2.76	2.56	2.52
Mg	0.53	0.59	0.49	0.46
Na	54.6	59.8	57.5	58.1
Κ	13	14.3	13.4	13.7
SO_4	437	460	458	456
S_2O_3	0.632	0.696	n.d.	n.d.
H_2S	1.03	0.04	0.01	< 0.005
Alkalinity (as HCO ₃)	n.a.	n.a.	n.a.	n.a.
F	2.95	3.24	3.21	3.23
Cl	8.69	9.48	9.14	9.23
Br	< 0.040	< 0.040	< 0.040	< 0.040
SiO ₂	221	235	236	239
NO ₃	< 0.031	< 0.031	< 0.031	< 0.031
NH_4	1.16	1.10	1.08	1.13
Al	5.65	6.49	5.85	6.10
Fe(total)	1.09	1.14	1.05	1.07
Fe(II)	1.09	1.14	1.05	1.07
В	0.64	0.78	0.64	0.72
Li	0.31	0.33	0.32	0.32
Sr	0.014	0.015	0.015	0.013
Ba	< 0.06	0.072	< 0.05	< 0.05
Mn	< 0.12	< 0.12	< 0.12	< 0.12
Zn	0.108	< 0.01	< 0.01	< 0.01
Pb	< 0.15	< 0.15	< 0.15	< 0.15
Be	< 0.001	< 0.001	< 0.001	< 0.001
V	< 0.02	< 0.02	< 0.02	< 0.02
Cr	< 0.09	< 0.09	< 0.09	< 0.09
Co	< 0.04	< 0.04	< 0.04	< 0.04
Ni	< 0.04	< 0.04	< 0.04	< 0.04
Cu	< 0.14	< 0.14	< 0.14	< 0.14
Cd	< 0.04	< 0.04	< 0.04	< 0.04
As(total)	0.19	0.21	0.21	0.21
DOC (mg/L)	1.8	1.9	1.5	1.5
Sum cations (meq/L)	8.3	9.1	8.7	8.6
Sum anions (meq/L)	6.7	7.6	7.8	7.9
Charge imbalance (percent) ¹	22.0/8.4	19.0/2.3	11.4/-0.3	9.5/-1.9

Table 4. Site data and water analyses for Frying Pan Spring and its overflow channel, Norris Geyser Basin

¹Where two charge imbalance values appear, they are field pH C.I./lab pH C.I.

Sample code number	94WA117	94WA118	94WA119
Date collected	6/29/94	6/29/94	6/29/94
Flow channel distance (m)	14.6	18.6	24.6
Temperature (°C)	47.4	46.2	45.7
Density (g/mL) at 20°C	0.99874	0.99901	0.99955
pH (field/lab)	2.28/2.38	2.31/2.40	2.3/2.40
Spec. cond. (µS/cm) (field/lab)	1795/2180	1802/2190	1820/2220
Eh (V)	0.359	0.270	0.326
D.O. (mg/L)	2.7	2.75	2.95
Constituent (mg/L)			
Ca	2.64	2.49	2.61
Mg	0.45	0.46	0.51
Na	58	57.4	59.3
К	13.6	12.8	13.7
SO_4	465	463	470
S_2O_3	n.a.	n.a.	0.550
H ₂ S	< 0.005	0.02	0.01
Alkalinity (as HCO_3)	n.a.	n.a.	n.a.
F	3.13	3.23	3.25
Cl	9.32	9.18	9.28
Br	< 0.040	< 0.040	< 0.040
SiO ₂	236	228	239
NO ₃	< 0.031	< 0.031	< 0.031
NH ₄	1.09	1.11	1.12
Al	5.97	5.87	6.04
Fe(total)	1.08	1.05	1.08
Fe(II)	1.08	1.05	1.08
В	0.69	0.77	0.73
Li	0.33	0.34	0.34
Sr	0.015	0.014	0.015
Ba	< 0.05	< 0.055	< 0.057
Mn	< 0.12	< 0.12	< 0.12
Zn	< 0.01	< 0.01	< 0.01
Pb	< 0.15	< 0.15	< 0.15
Be	< 0.001	< 0.001	< 0.001
V	< 0.02	< 0.02	< 0.02
Cr	< 0.09	< 0.09	< 0.09
Со	< 0.04	< 0.04	< 0.04
Ni	< 0.04	< 0.04	< 0.04
Cu	< 0.14	< 0.14	< 0.14
Cd	< 0.04	< 0.04	< 0.04
As(total)	0.22	0.21	0.22
DOC (mg/L)	1.5	1.6	1.6
Sum cations (meq/L)	9.2	8.8	9.0
Sum anions (meq/L)	7.9	8.0	8.1
Charge imbalance (percent) ¹	15.2/-1.7	9.8/-5.2	11.3/-5.1

Table 4. Site data and water analyses for Frying Pan Spring and its overflow channel, Norris Geyser Basin--continued

¹Where two charge imbalance values appear, they are field pH C.I./lab pH C.I.

$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
Temperature (°C)71.470.661.956.5Density (g/mL) at 20°C1.000130.999990.999960.99975pH (field/lab) $6.43/8.47$ $6.51/8.37$ $7.14/8.47$ $7.52/8.32$ Spec. cond. (µS/cm) (field/lab)2170/23402195/23402230/20902245/1810Eh (V)-0.041-0.0300.1580.178D.O. (mg/L)0.51.12.22.9Constituent (mg/L)0.51.12.22.9Ca320308298270Mg74.873.273.472.9Na136132133132K57.458.557.953.6SQ4547544553557s2O3<0.09
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c cccc} \begin{tabular}{ cccccc ccccccccccccccccccccccccccccc$
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
Ca320308298270Mg74.873.273.472.9Na136132133132K57.458.557.953.6SO4547544553557 s_2O_3 <0.09
Mg74.873.273.472.9Na136132133132K 57.4 58.5 57.9 53.6 SO4 547 544 553 557 s_2O_3 <0.09 0.452 0.620 0.553 H_2S 3.01 0.95 0.33 0.09 Alkalinity (as HCO3) 734 734.5 629.1 633.7 F 2.93 2.72 2.35 1.98 Cl165166168170Br 0.554 0.561 0.568 0.573 SiO2 54 51.9 58.4 54.4 NO3 0.034 <0.031 <0.031 <0.031 NH4 0.913 0.863 0.873 0.881 Al 0.012 0.010 0.007 0.006 Fe(tot) 0.0297 0.0253 0.0055 0.0025
Na136132133132K 57.4 58.5 57.9 53.6 SO4 547 544 553 557 s_2O_3 <0.09 0.452 0.620 0.553 H_2S 3.01 0.95 0.33 0.09 Alkalinity (as HCO3) 734 734.5 629.1 633.7 F 2.93 2.72 2.35 1.98 Cl165166168170Br 0.554 0.561 0.568 0.573 SiO2 54 51.9 58.4 54.4 NO3 0.034 <0.031 <0.031 <0.031 NH4 0.913 0.863 0.873 0.881 Al 0.012 0.010 0.007 0.006 Fe(tot) 0.0297 0.0253 0.0055 0.0025
K57.458.557.953.6 SO_4 547544553557 S_2O_3 <0.09
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
$\begin{array}{c c c c c c c c c c c c c c c c c c c $
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
NH_4 0.9130.8630.8730.881Al0.0120.0100.0070.006Fe(tot)0.02970.02530.00550.0025
Al0.0120.0100.0070.006Fe(tot)0.02970.02530.00550.0025
Fe(tot) 0.0297 0.0253 0.0055 0.0025
Fe(II) 0.0297 0.0253 0.0055 0.0025
B 3.56 3.5 3.6 3.48
Li 1.64 1.66 1.67
Sr 1.63 1.59 1.49 1.31
Ba <0.1 <0.1 <0.1 <0.1
Mn <0.3 <0.3 <0.3 <0.3
Zn <0.025 <0.025 <0.025 <0.025
Pb <0.375 <0.375 <0.375 <0.375
Be <0.001 <0.001 <0.001 <0.001
V <0.05 <0.05 <0.05 <0.05
Cr <0.225 <0.225 <0.225 <0.225
Co <0.1 <0.1 <0.1 <0.1
Ni <0.1 <0.1 <0.1 <0.1
Cu <0.35 <0.35 <0.35 <0.35
Cd <0.1 <0.1 <0.1 <0.1
As(total) 0.47 0.42 0.55 0.62
DOC (mg/L) 1.1 1.1 0.8 n.a.
Sum cations (meq/L) 24.3 23.5 23.2 21.7
Sum anions (meq/L) 22.5 22.6 21.2 21.6
Charge imbalance (percent) 7.5 3.9 8.7 0.5

Table 5. Site data and water analyses for Angel Terrace Spring and its overflow channel, Mammoth Hot Springs complex

Sample code number	95WA101	95WA101A	95WA101B	95WA102	95WA103
Date collected	8/20/95	8/20/95	(unfiltered) 8/20/95	8/20/95	8/20/95
Flow channel distance (m)	64	64	64	25	42
Temperature (°C)	72.8	$(75)^{1}$	(75)	<u> </u>	(64)
Density (g/mL) at 20°C	n.a.	0.9992	0.9993	0.9991	0.9989
pH (field/lab)	8.75/9.21	n.m./9.29	n.m./9.28	8.76/9.26	8.77/9.28
Spec. cond. (uS/cm) (field/lab)	1510	n.m./1652	n.m./1575	1530/1577	1520/1578
Eh (V)	-0.038	n.m.	n.m.	-0.026	0.016
D.O. (mg/L)	n.m.	n.m.	n.m.	n.m.	n.m.
Constituent (mg/L)					
Ca	1.5	1.9	1.7	1.3	1.4
Mg	0.0056	0.0095	0.0118	0.0065	0.0061
Na	315	346	321	318	316
K	13.5	13.8	13.8	13.5	13.7
SO_4	41	44	46	43	45
S_2O_3	5.26	n.a.	n.a.	4.49	4.08
H_2S	0.36	n.a.	n.a.	0.237	0.149
Alkalinity (as HCO ₃)	206	205.6	206.8	198.5	199.3
F	30.1	31.9	31.0	30.6	31.1
Cl	306	310	305	308	316
Br	0.9	0.8	0.9	1.0	1.1
SiO ₂	294	277	272	293	283
NO ₃	0.96	1.01	1.07	1.07	1.06
NH_4	0.05	0.06	n.a.	0.06	0.01
Al	0.200	0.205	0.241	0.218	0.200
Fe(total)	0.030	0.025	0.026	0.035	0.027
Fe(II)	0.030	0.023	0.026	0.035	0.027
B	4.30	4.70	4.80	4.40	4.38
Li	2.91	3.21	2.95	2.83	2.87
Sf	0.010	0.015	0.015	0.010	0.008
Ba	< 0.015	< 0.015	< 0.015	< 0.015	< 0.015
	< 0.010	< 0.000	< 0.006	< 0.011	<0.010
ZII Dh	0.009 <0.11	< 0.010	< 0.009	0.009	0.009 <0.11
ru Be	<0.11	<0.11	<0.11	<0.01	<0.11
V	<0.001	<0.001	<0.001	<0.001	<0.001
Cr.	<0.021	<0.021	<0.021	<0.021	<0.021
Co	<0.21	<0.021	<0.021	<0.21	<0.021
Ni	<0.024	<0.024	<0.024	<0.024	<0.024
Cu	<0.070	<0.012	<0.20	<0.070	<0.070
Cd	<0.20	<0.009	<0.009	<0.009	0.011
As(total)	1.5	1.5	1.7	1.4	1.9
DOC	n.a.	n.a.	n.a.	n.a.	n.a.
Sum cations (meg/L)	14.39	15.94	14.79	15.54	14.47
Sum anions (meq/L)	14.38	14.76	14.57	14.41	14.73
Charge imbalance (percent)	0.11	7.64	1.51	0.90	-1.78

Table 6. Site data and water analyses for Azure Spring and its overflow channel, Lower Geyser Basin

¹Temperatures in () were estimated from data collected 8/18/96.

Sample code number	95WA104	95WA105	95WA106	95WA107	95WA108
	(unfiltered)	(unfiltered)	(unfiltered)	(unfiltered)	(unfiltered)
Date collected	8/20/95	8/19/95	8/20/95	8/20/95	8/20/95
Flow channel distance (m)	57	85	107	132	168
Temperature (°C)	n.m.	$(57)^{1}$	n.m.	n.m.	n.m.
Density (g/mL) at 20°C	0.9990	0.9991	0.9991	0.9991	0.9990
pH (field/lab)	n.m./9.32	8.95/9.29	n.m./9.29	n.m./9.31	n.m./9.30
Spec. cond. (µS/cm) (field/lab)	n.m./1572	n.m./1607	n.m./1607	n.m./1613	n.m./1632
Eh (V)	n.m.	0.039	n.m.	n.m.	n.m.
D.O. (mg/L)	n.m.	n.m.	n.m.	n.m.	n.m.
Constituent (mg/L)					
Ca	1.40	1.41	1.44	1.49	1.48
Mg	0.0084	0.0120	0.0161	0.0090	0.0074
Na	317	325	327	325	327
K	13.5	13.7	14.0	14.3	14.7
SO_4	45	46	47	45	52
S ₂ O ₃	4.08	3.64	4.04	4.12	2.23
H ₂ S	0.143	0.047	0.086	0.064	0.011
Alkalinity (as HCO_3)	200.4	201.9	201.6	202.4	204.2
F	41.4	43.3	43.5	44.0	44.0
	311	314	312	305	310
Br	<0.3	0.8	0.9	0.9	0.9
	294	291	286	287	289
NO ₃	0.98	0.99	0.82	0.76	1.11
	0.02	< 0.01	0.07	0.01	< 0.01
AI Es(total)	0.209	0.216	0.299	0.205	0.195
Fe(total)	0.025	0.026	0.038	0.025	0.022
B	0.025	0.020	4 35	0.025	4.50
	2 98	4.50	3.09	4.74	4.50
Sr.	0.008	0.008	0.009	0.013	0.014
Ba	<0.000	<0.000	<0.005	<0.015	<0.014
Mn	<0.019	<0.015	<0.015	<0.015	<0.008
Zn	< 0.009	< 0.009	< 0.009	< 0.009	< 0.009
Pb	< 0.11	< 0.11	< 0.11	< 0.11	< 0.11
Be	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001
V	< 0.021	< 0.021	< 0.021	< 0.021	< 0.021
Cr	< 0.21	< 0.21	< 0.21	< 0.21	< 0.21
Со	< 0.024	< 0.024	< 0.024	< 0.024	< 0.024
Ni	< 0.070	< 0.042	< 0.042	< 0.042	< 0.042
Cu	< 0.20	< 0.20	< 0.20	< 0.20	< 0.20
Cd	< 0.009	< 0.009	< 0.009	< 0.009	< 0.009
As(total)	1.9	1.7	1.5	1.7	1.7
DOC	n.a.	n.a.	n.a.	n.a.	n.a.
Sum cations (meq/L)	14.61	14.89	15.05	14.97	15.06
Sum anions (meq/L)	15.14	15.37	15.35	15.15	15.46
Charge imbalance (percent)	-3.56	-3.15	-1.96	-1.15	-2.66

Table 6. Site data and water analyses for Azure Spring and its overflow channel, Lower Geyser Basin--continued

¹Temperatures in () were estimated from data collected 8/18/96.

Table 7. Site data and water analyses for miscellaneous springs

Name	Fchinus	Cinder Pool	Black Pool	Unnamed
Ivanie	Gevser Norris	Norris Gevser	Norris Gever	drainage
	Gevser Basin	Basin	Basin	Brimstone
	Geyser Bushi	Dusin	Dusin	Basin
Sample code number	95WA109	95WA110	95WA116	95WA114
Date collected	8/22/95	8/22/95	8/25/95	8/24/95
Temperature (°C)	85	95	89.2	6.5
Density (α/mL) at 20°C	0 9990	0 9993	0 9993	0 9991
pH (field/lab)	3 53/3 33	4 22/3 95	2 61/2 54	2 84/2 86
Spec cond (uS/cm) (field/lab)	1090/1230	n m /2320	1980/2990	1473/1315
Eh (V)	0 336	0.022	0.127	0 473
DO(mg/L)	n m	0.5	n m	n m
Constituent (mg/L)	11.111.	0.5	11.111.	11.111.
Ca	51	59	24	32.0
Mg	0.690	0.024	0 182	21.4
Na	160	373	293	14.2
K	54.8	57.6	71.4	17.8
SO ₄	296	96	300	602
S_2O_2	0.03	5.10	0.02	n.a.
H_2S	0.03	1.6	1.6	2.6
Alkalinity (as HCO ₃)	n.a.	n.a.	n.a.	n.a.
F	5.11	6.24	5.28	0.364
Cl	109	601	463	0.6
Br	0.3	1.7	1.4	< 0.3
SiO ₂	335	433	426	90.4
NO ₃	0.55	1.63	1.41	0.37
NH ₄	2.1	18	19	0.34
Al	2.00	1.13	6.10	51.0
Fe(tot)	2.63	0.088	2.15	5.33
Fe(II)	2.62	0.088	2.15	5.28
В	2.31	9.60	8.50	< 0.20
Li	0.840	4.70	4.24	0.040
Sr	0.006	0.011	0.008	0.650
Ba	0.065	< 0.025	0.090	< 0.015
Mn	0.280	< 0.006	0.06	0.51
Zn	0.050	< 0.009	0.016	< 0.009
Pb	< 0.11	< 0.11	< 0.11	< 0.11
Be	0.006	< 0.001	< 0.001	< 0.001
V	< 0.021	< 0.021	< 0.02	0.05
Cr	< 0.21	< 0.21	< 0.21	< 0.21
Со	< 0.024	< 0.024	< 0.024	< 0.024
Ni	< 0.042	< 0.042	< 0.04	< 0.04
Cu	< 0.20	< 0.20	< 0.20	< 0.20
Cd	< 0.009	< 0.009	< 0.009	< 0.009
As(total)	0.29	2.4	1.5	< 0.001
DOC	n.a.	n.a.	n.a.	n.a.
Sum cations (meq/L)	9.18	19.70	19.51	8.44
Sum anions (meq/L)	8.82	19.09	17.87	8.78
Charge imbalance (percent)	3.96	3.16	8.80	-3.93

Name	Unnamed	Acid Ink Pot,	Unnamed	Unnamed acid
	drainage,	Washburn Hot	spouter,	spring, Washburn
	Brimstone	Springs complex	Washburn Hot	Hot Springs
	Basin		Springs complex	complex
Sample code number	¹ 95WA115	95WA111	95WA112	95WA113
Date collected	8/24/95	8/23/95	8/23/95	8/23/95
Temperature (°C)	8	75.5	93	82
Density (g/mL) at 20°C	0.9987	1.0012	0.9995	1.0019
pH (field/lab)	4.79/4.03	2.92/2.49	6.71/6.77	1.83/1.63
Spec. cond. (µS/cm) (field/lab)	n.m/758	5790/7260	3250/3300	7670/13600
Eh (V)	0.337	0.067	0.157	0.223
D.O. (mg/L)	n.m.	0.3	n.m.	n.m.
Constituent (mg/L)				
Ca	40.3	42	7.0	14.6
Mg	41.0	19.7	4.40	9.30
Na	11.7	31.0	11.0	11.0
K	11.9	18.3	12.5	13.1
SO_4	430	3120	1280	4200
S_2O_3	n.a.	0.09	0.13	n.a.
H ₂ S	0.4	8	< 0.03	5.7
Alkalinity (as HCO_3)	7.23	n.a.	9.25	n.a.
F	0.410	0.338	0.222	0.182
Cl	0.4	<10	1.8	6.7
Br	< 0.3	<22	< 0.2	< 0.2
SiO ₂	88.0	262	263	316
NO ₃	0.38	0.26	0.30	0.42
NH ₄	0.19	884	478	628
Al	27.5	34.0	0.820	68.0
Fe(tot)	6.42	23.6	2.22	71.0
Fe(II)	6.35	23.6	2.21	65.0
В	< 0.20	9.40	14.3	15.0
Li	< 0.055	0.050	0.050	< 0.070
Sr	0.530	0.240	0.050	0.490
Ва	< 0.015	0.030	< 0.015	0.070
Mn	0.96	0.510	0.120	0.34
Zn	< 0.009	0.080	< 0.009	0.060
Pb	< 0.11	< 0.11	< 0.11	< 0.11
Be	< 0.001	< 0.001	< 0.001	< 0.001
V	< 0.02	0.050	< 0.021	0.11
Cr	< 0.21	< 0.21	< 0.21	< 0.21
Со	< 0.024	< 0.024	< 0.024	0.060
Ni	< 0.04	< 0.042	< 0.042	0.18
Cu	< 0.20	< 0.20	< 0.20	< 0.20
Cd	< 0.009	< 0.009	< 0.009	< 0.009
As(total)	< 0.001	< 0.001	< 0.001	< 0.001
DOC	n.a.	n.a.	n.a.	n.a.
Sum cations (mea/L)	7.16	51.12	26.06	57.90
Sum anions (mea/L)	6.75	51.18	24.78	50.81
Charge imbalance (percent) ²	5.97	-0.11	5.04	13.1/-21.4

Table 7. Site data and water analyses for miscellaneous springs--continued

¹This unfiltered sample contained visible colloidal precipitate. ²Where two charge imbalance values appear, they are field pH C.I./lab pH C.I.

Table 8. ²H and ¹⁸O isotope analyses

Name	Sample code	$\delta^2 H^*$	$\delta^{18}O^{\ast}$
Ojo Caliente at source	94WA100	-142	-16.4
Ojo Caliente at pool outflow	94WA101	-139	-16.3
Ojo Caliente overflow channel	94WA104	-140	-16.3
Ojo Caliente overflow channel	94WA106	-139	-16.2
Ojo Caliente overflow channel	94WA107	-139	-16.1
Ojo Caliente overflow channel	94WA108	-140	-16.1
Ojo Caliente overflow channel	94WA110	-138	-15.9
Ojo Caliente overflow channel	94WA112	-136	-15.4
Frying Pan Spring at source	94WA113	-123	-11.9
Frying Pan Spring overflow channel	94WA114	-121	-10.7
Frying Pan Spring overflow channel	94WA116	-119	-10.8
Frying Pan Spring overflow channel	94WA119	-119	-10.5
Angel Terrace Spring at source	94WA120	-148	-18.2
Angel Terrace Spring in pool	94WA121	-148	-18.2
Angel Terrace Spring pool outlet	94WA122	-146	-17.9
Azure Spring overflow channel	95WA101	-141	-15.9
Azure Spring overflow channel	95WA101A	-142	-15.5
Azure Spring overflow channel	95WA101B	-139	-15.5
Azure Spring overflow channel	95WA102	-138	-15.7
Azure Spring overflow channel	95WA103	-138	-15.6
Azure Spring overflow channel	95WA104	-139	-15.6
Azure Spring overflow channel	95WA105	-137	-15.3
Azure Spring overflow channel	95WA106	-138	-15.4
Azure Spring overflow channel	95WA107	-134	-15.2
Azure Spring overflow channel	95WA108	-133	-15.0
Echinus Geyser, Norris Geyser Basin	95WA109	-137	-16.4
Cinder Pool, Norris Geyser Basin	95WA110	-124	-10.7
Black Pool, Norris Geyser Basin	95WA116	-122	-9.7
Unnamed drainage, Brimstone Basin, upper site	95WA114	-140	-18.6
Unnamed drainage, Brimstone Basin, lower site	95WA115	-139	-18.9
Acid Ink Pot, Washburn Hot Springs	95WA111	-106	-4.0
Unnamed spouter, Washburn Hot Springs	95WA112	-115	-6.5
Unnamed acid spring, Washburn Hot Springs	95WA113	-119	-7.3

*Permil relative to VSMOW.

		SO4	H ₂ S	S_2O_3	Cl
Location and Data Source	Date		· mg	/L	
Ojo Caliente			0		
Allen and Day (1935)		29	n.m.	5	324
Thompson and others (1975)	Jun 1966	n.m.	n.m.	n.m.	345
Thompson and others (1975)	Jun 1967	27	n.m.	n.m.	331
Thompson and others (1975)	Sep 1972	24	1.3	n.m.	331
Thompson and DeMonge (1996)	Oct 1979	22	0.11	n.m.	338
Thompson and DeMonge (1996)	Oct 1981	14	0.29	n.m.	318
Thompson and DeMonge (1996)	Sep 1986	28	0.3	n.m.	326
Thompson and DeMonge (1996)	Sep 1990	15	0.28	n.m.	312
This study	Jun 1994	21	1.09	0.27	324
Azure Spring					
Stauffer and others (1980)	Sep 1974	50	1.5	n.m.	310
This study	Aug 1995	41	0.36	5.26	306
<u>Frying Pan Spring</u>					
Allen and Day (1935)		486	n.m.	n.m.	4
Thompson and others (1975)	Sep 1973	335	n.m.	n.m.	39
This study	Jun 1994	437	1.03	0.63	8.7
Angel Terrace		100			150
Allen and Day (1935)	I 1004	490	n.m.	n.m.	178
This study	Jun 1994	547	3.01	0-0.6	165
Echinus Geyser	A	222	440.00		101
Gooch and Whitfield (1888)	Aug 1884	232	trace	n.m.	121
Scoll (1904) White (unruch date)		310 296	n.m.	n.m.	105
white (unpub. data)		280	n.m.	n.m.	108
Rowe and others (1973)		284	n.m.	n.m.	108
Rowe and others (1973)		280	n.m.	n.m.	115
Thempson and others (1975)	Oct 1067	270	n.m.	11.111. n.m.	107
Thompson and Vaday (1973)	Oct 1907	370	n.m.	11.111. n.m	100
Thompson and DeMonge (1006)		120,260	11.111.	11.111. n m	105
Thompson and Demonge (1990)		120-300	0.01-0.12	0.02	107-134
		290	0.03	0.03	109
Cinder Pool					
White (uppub data)	Sep 1947	n m	n m	n m	668
White (unpub. data)	Sep 1947	n.m.	n m	n m	790
White (unpub. data)	Sep 1960	125	n m	n m	727
Rowe and others (1973)	Sep 1900	87	n m	n m	720
Thompson and DeMonge (1996)		147	n m	n m	569
This study		96	1.6	$^{1}5.1$	601
Thompson and Others (1973) Thompson and Yadav (1979) Thompson and DeMonge (1996) This study <u>Cinder Pool</u> White (unpub. data) White (unpub. data) White (unpub. data) Rowe and others (1973) Thompson and DeMonge (1996) This study	Sep 1947 Sep 1957 Sep 1960	273 120-360 296 n.m. n.m. 125 87 147 96	n.m. 0.01-0.12 0.03 n.m. n.m. n.m. n.m. n.m. 1.6	n.m. n.m. 0.03 n.m. n.m. n.m. n.m. n.m. 15.1	100 103 107-154 109 668 790 727 720 569 601

Table 9. Comparison of historic data on sulfur species concentrations for selected locations

 ${}^{1}S_{4}O_{6} \approx 1 \text{ mg/L}.$

REFERENCES CITED

- Aiken, G. R., 1992, Chloride interference in the analysis of dissolved organic carbon by the wet oxidation method: Environmental Science and Technology, v. 26, p. 2435-2439.
- Allen, E. T., and Day, A. L., 1935, Hot springs of the Yellowstone National Park: Carnegie Institution of Washington Publication Number 466, 525 p.
- American Public Health Association (APHA), 1985, Method 428C. Methylene blue method for sulfide *in* American Public Health Association, Standard methods for the examination of water and wastewater (14th ed.), p. 403-405.
- Ball, J. W., Nordstrom, D. K., Jenne, E. A., and Vivit, D. V., 1998, Chemical Analyses of hot springs, pools, geysers, and surface waters from Yellowstone National Park, Wyoming, and vicinity, 1974-1975: U.S. Geological Survey Open-File Report 98-182, 45 p.
- Ball, J. W., and Nordstrom, D. K., 1991, User's manual for WATEQ4F, with revised thermodynamic data base and test cases for calculating speciation of major, trace, and redox elements in natural waters: U.S. Geological Survey Open-File Report 91-183, 189 p.
- Barnard, W. R., and Nordstrom, D. K., 1980, Fluoride in precipitation-I. Methodology with the fluoride-selective electrode: Atmospheric Environment, v. 16, p. 99-103.
- Chen, K. Y., and Morris, J. C., 1972, Kinetics of oxidation of aqueous sulfide by O₂: Environmental Science and Technology, v. 6, p. 529-537.
- Coplen, T. B., Wildman, J. D., and Chen, J., 1991, Improvements in the gaseous hydrogen-water equilibrium technique for hydrogen isotope ratio analysis: Analytical Chemistry, v. 63, p. 910-912.
- Epstein, S. and Mayeda, T., 1953, Variation of ¹⁸O content of water from natural sources: Geochimica et Cosmochimica Acta, v. 4, p. 213-224.
- Fishman, M. J., and Friedman, L. C., eds., 1989, Methods for determination of inorganic substances in water and fluvial sediments. Techniques of water-resources investigations of the U.S. Geological Survey, Bk. 5., Chap. A1, p. 55-56.
- Fournier, R. O., 1989, Geochemistry and dynamics of the Yellowstone National Park hydrothermal system: Annual Review of Earth and Planetary Sciences, v. 17, p. 13-53.
- Fournier, R. O., Thompson, J. M., and Hutchinson, R. A., 1994, The geochemistry of hot spring waters at Norris Geyser Basin, Yellowstone National Park: Geothermal Resources Council T., v. 18, p. 177-179.
- Gooch, F. A., and Whitfield, J. E., 1888, Analyses of waters of the Yellowstone National Park with an account of the methods of analysis employed: U.S. Geological Survey Bulletin 47, 84 p.

- Kharaka, Y. K., Mariner, R. H., Bullen, T. D., Kennedy, B. M., and Sturchio, N. C., 1991, Geochemical investigations of hydraulic connections between the Corwin Springs Known Geothermal Resources Area and adjacent parts of Yellowstone National Park: *in* Sorey, M. L., ed., Effects of potential geothermal development in the Corwin Springs Known Geothermal Resources Area,: U.S. Geological Survey Water-Resources Investigations Report 91-4052, p. F-1 F-38.
- Kennedy, V. C., Jenne, E. A., and Burchard, J. M., 1976, Back-flushing filters for field processing of water samples prior to trace-element analyses: U.S. Geological Survey Open-File Report 76-126, 12 p.
- Nordstrom, D. K., 1977, Thermochemical redox equilibria of ZoBell's solution: Geochimica et Cosmochimica Acta, v. 41, p. 1835-41.
- O'Brien, D. J., and Birkner, F. B., 1977, Kinetics of oxygenation of reduced sulfur species in aqueous solution: Environmental Science and Technology, v. 11, p. 1114-1120.
- Reardon, J., Foreman, J. A., and Searcy, R. L., 1966, New reactants for the colorimetric determination of ammonia: Clinica Chimica Acta, v. 14, no. 3, p. 403-405.
- Rolla, E. and Chakrabarti, C. L., 1982, Kinetics of decomposition of tetrathionate, trithionate, and thiosulfate in alkaline media: Environmental Science and Technology, v. 16, p. 852-857.
- Rowe, J. J., Fournier, R. O., and Morey, G. W., 1973, Chemical analysis of thermal waters in Yellowstone National Park, Wyoming, 1960-65: U.S. Geological Survey Bulletin 1303, 31 p.
- Scott, R. C., 1964, Records in post earthquake quality of groundwater, *in* The Hebgen Lake, Montana, earthquake of August 17, 1959: U.S. Geological Survey Professional Paper 435, p. 179-184.
- Shapiro, L., and Brannock, W. W., 1962, Rapid analysis of silicate, carbonate, and phosphate rocks: U.S. Geological Survey, Bulletin 1144-A, 56 p.
- Smith, R. M., and Martell, A. E., 1976, Critical stability constants. Volume 4: Inorganic complexes: New York, Plenum Press, p. 76-77.
- Solorzano, L., 1969, Determination of ammonia in natural waters by the phenolhypochlorite method: Limnology and Oceanography, v. 5, p. 799-801.
- Stauffer, R. E., Jenne, E. A., and Ball, J. W., 1980, Chemical studies of selected trace elements in hot-spring drainages of Yellowstone National Park: U.S. Geological Survey Professional Paper 1044-F, 20 p.
- Stookey, L. L., 1970, Ferrozine a new spectrophotometric reagent for iron: Analytical Chemistry, v. 42, p. 779-781.

- Thompson, J. M., and DeMonge, J. M., 1996, Chemical analyses of hot springs, pools, and geysers from Yellowstone National Park, Wyoming, and vicinity, 1980-1993: U.S. Geological Survey Open-File Report 96-68, 66 p.
- Thompson, J. M., and Hutchinson, R. A., 1981, Chemical analyses of waters from the Boundary Creek Thermal Area, Yellowstone National Park, Wyoming: U.S. Geological Survey Open-File Report 81-1310, 15 p.
- Thompson, J. M., Presser, T. S., Barnes, R. B., and Bird, D. B., 1975, Chemical analysis of the waters of Yellowstone National Park, Wyoming from 1965 to 1973: U.S. Geological Survey Open-File Report 75-25, 58 p.
- Thompson, J. M., and Yadav, S., 1979, Chemical analysis of waters from geysers, hot springs and pools in Yellowstone National Park, Wyoming from 1974 to 1978: U.S. Geological Survey Open-File Report 79-704, 48 p.
- White, D. E., Hem, J. D., and Waring, G. A., 1963, Chemical composition of subsurface waters, *in* Data of Geochemistry, 6th edition: U.S. Geological Survey Professional Paper 440-F, 67 p.
- White, D. E., Hutchinson, R. A., and Keith, T. E. C., 1988, The geology and remarkable thermal activity of Norris Geyser Basin, Yellowstone National Park: U.S. Geological Survey Professional Paper 1456, 84 p.
- Xu, Y., and Schoonen, M. A. A., 1995, The stability of thiosulfate in the presence of pyrite in lowtemperature aqueous solutions: Geochimica et Cosmochimica Acta, v. 59, p. 4605-4622.
- Xu, Y., Schoonen, M. A. A., and Strongin, D. R., 1996, Thiosulfate oxidation: catalysis of synthetic sphalerite doped with transition metals: Geochimica et Cosmochimica Acta, v. 60, no. 23, p. 4701-4710.
- Xu, Y., Schoonen, M. A. A., Nordstrom, D. K., Cunningham, K. M., and Ball, J. W., 1998, Sulfur geochemistry of hydrothermal waters in Yellowstone National Park: I. The origin of thiosulfate in hot spring waters: Geochimica et Cosmochimica Acta, v. 62, p. 3729-3743.
- Xu, Y., Schoonen, M. A. A., Nordstrom, D. K., Cunningham, K. M., and Ball, J. W., 2000, Sulfur geochemistry of hydrothermal waters in Yellowstone National Park: II. Formation and decomposition of thiosulfate and polythionate in Cinder Pool: J. Volcanol. Geotherm. Res., v. 97, p. 407-423.
- Zhang, J. -Z., and Millero, F. J., 1994, Kinetics of oxidation of hydrogen sulfide in natural waters in Alpers, C. N. and Blowes, D. W., eds., Environmental geochemistry of sulfide oxidation: Washington, District of Columbia, The American Chemical Society, ACS Symposium Series 550, p. 393-409.
- ZoBell, C. E., 1946, Studies on redox potential of marine sediments: 8. Other methods: Bulletin of the American Association of Petroleum Geologists, v. 30, p. 477-509.

APPENDIX

Parameter or Element	Descriptor
pH	PH
Spec. cond.	COND
Eh	EC1
D. O.	EC2
Ca	ICP, FAAS
Mg	ICP, FAAS, ZGFAAS
Na	ICP, FAAS
K	ICP, FAAS
\mathbf{SO}_4	IC1
S_2O_3	IC2
H_2S	COLOR1
Alkalinity	TITR
F	IC1, EC3
Cl, Br	IC1
SiO_2	ICP, COLOR2
NO ₃	IC1
NH_4	COLOR3, COLOR4, IC3
Al	ICP, ZGFAAS
Fe (total)	ICP, COLOR5
Fe (II)	COLOR5
В	ICP
Li	FAAS
Sr, Ba, Mn, Zn, Pb, Be, V	ICP
Cr, Co, Ni, Cu, Cd	ICP
As (total)	ICP, FIAS
Dissolved organic carbon	DOC
$\delta^2 H$	ISOT1
$\delta^{18}O$	ISOT2

Table 10. Methods of analysis

Table 11. Explanation of methods of analysis [rsd, relative standard deviation]

Descriptor	Species Determined	Analyst(s)	Equipment Used	Reference(s) or comments	Typical rsd or detection limit (mg/L)
COLOR1	H_2S	Cunningham	Hach model DR-2000 UV-Vis absorption spectrometer and Hach method # 8131 reagents	Method based on APHA (1985)	0.005
COLOR2	SiO ₂	Cunningham	Hach model DR-2000 UV-Vis absorption spectrometer	Method based on Shapiro and Brannock (1962)	3% , 0.4
COLOR3	NH ₄	R.C. Antweiler, USGS, Boulder, CO	Alpkem model RFA-300 flow injection analyzer	Method based on Solorzano (1969)	3% , 0.012
COLOR4	NH_4	Cunningham	Hach model DR-2000 UV-Vis absorption spectrometer and Hach method # 8155	Method based on Reardon and others (1966)	
COLOR5	Fe(II) and Fe(total)	Ball	Hewlett-Packard model 8452A diode array spectrometer (1992-1994) with 1 and 5 cm cells	Ferrozine method (Stookey, 1970)	3% , 0.0005
COND	Spec. Cond.	Authors	Orion Research model 126 meter	Automatic temperature correction, conductance check with 0.0100 N KCl	≤0.5%
DOC	DOC	G.R. Aiken, USGS, Boulder, CO	Oceanography International model 700 carbon analyzer	Some samples were diluted to reduce interference from Cl ⁻ (Aiken, 1992)	~ 10% , <i>0</i> .2
EC1	Eh	Nordstrom, Ball	Orion Research model 96-78-00 Pt electrode	Electrode checked using ZoBell's solution (ZoBell, 1946; Nordstrom, 1977), at the sample temperature	
EC2	D.O.	Authors	Orion Research model 840 DO meter and probe	Automatic sample temperature and barometric pressure correction	1%
EC3	F⁻	Nordstrom	Orion Research model 96-09 comb. F ⁻ electrode	Barnard and Nordstrom (1980)	~3%

Table 11. Explanation of methods of analysis--continued

Descriptor	Species Determined	Analyst(s)	Equipment Used	Reference(s) or comments	Typical rsd , <i>detection limit</i> (<i>mg/L</i>)
FAAS	Na, K, Ca, Mg, and Li	Cunningham	Perkin-Elmer model 5000 flame atomic absorption spectrometer with air/acetylene flame, single-slot burner head, and continuum background correction, in absorption (Ca, Mg, Li, Na, K) or emission (Na*, K*) mode	1000 mg/L Cs ionization buffer.	~2% Na: 0.005(0.040*) K : 0.025(0.007*) Ca: 0.030 Mg: 0.030 Li: 0.003
FIAS	As(total)	Cunningham	Perkin-Elmer model 5000 atomic absorption spectrometer in absorption mode with a FIAS-200 flow injection analysis system hydride generator, quartz cell, and furnace	Pre-reduction of As(V) using KI + HCl	~ 10% , <i>0.001</i>
IC1	F , CI , SO_4^{2-} , NO_3^{-} , and Br^{-}	Schoonen, Xu, Cunningham	Dionex model 2000i/2010i ion chromatograph with AG4A guard and AS4A separator columns and an Anion Micromembrane Suppressor-II column	0.028 M NaHCO ₃ + 0.022 M Na ₂ CO ₃ eluent	2-3% , $F = 0.03$, $Cl^{-} = 0.05$, $SO_{4}^{2-} = 0.16$, $NO_{3}^{-} = 0.09$, $Br^{-} = 0.11$
IC2	S ₂ O ₃ ²⁻	Schoonen, Xu	Dionex model 2000i/2010i ion chromatograph with two AG4A guard columns and AS4A separator column and an Anion Micromembrane Suppressor-II column	0.028 M NaHCO ₃ + 0.022 M Na ₂ CO ₃ eluent	2-3%, 0.09
IC3	$ m NH_4$	B. Kumler, USGS, Boulder, CO	Dionex model DX-300 ion chromatograph with CS12A IonPac column and 22 mN H_2SO_4 eluent	Analysis performed on year-old samples preserved in 1% HCl	~2%

Descriptor	Species Determined	Analyst(s)	Equipment Used	Reference(s) or comments	Typical rsd or detection limit (mg/L)
ICP	Al. As. B.	Cunningham	Leeman Labs Plasma-Spec III, simultaneous, multi-	Analytical wavelengths -	~2% for all
-	Ba, Be, Ca,	6	element, inductively coupled plasma spectrometer.	nanometers:	elements
	Cd, Co, Cr,		Hildebrand grid nebulizer and polyethylene spray	Al - 309.27	Al: 0.220
	Cu, Fe(total),		chamber. RF frequency - 27.5 MHZ at 1 kw. Ar	As - 193.70	As: 0.170
	K, Mg, Mn,		coolant and nebulizer gas. Inter-element interferences	B - 249.68	B: 0.090
	Na, Ni, Pb,		were corrected with MEGACRUNCH software (J.W.	Ba - 455.40	Ba: 0.020
	Si, Sr, V, Zn		Ball, unpub. data).	Be - 313.04	Be: 0.001
				Ca - 315.90	Ca: 0.050
				Cd - 214.44	Cd: 0.020
				Co - 228.62	<i>Co: 0.020</i>
				Cr - 205.55	Cr: 0.045
				Cu - 324.75	<i>Cu: 0.070</i>
				Fe - 238.20	Fe: 0.150
				K - 766.46	K: 0.870
				Mg - 279.08	Mg: 0.090
				Mn - 257.61	Mn: 0.060
				Na - 589.59	Na: 0.400
				Ni - 231.60	Ni: 0.020
				Pb - 220.35	Pb: 0.075
				Si - 288.16	Si: 1.02
				Sr - 407.77	Sr: 0.001
				V - 292.40	V:0.010
				Zn - 213.86	Zn: 0.005
ISOT1	$\delta^2 H$	T.B. Coplen and J.A. Hopple, USGS, Reston, VA (1994 samples) and C. Kendall, USGS, Menlo Park, CA (1995 samples)	V.G. Micromass model 602 mass spectrometer	Coplen and others (1991). Standardization against VSMOW ($\delta^2 H = 0$ per mil) and SLAP ($\delta^2 H =$ -428 per mil)	1.5 per mil

Table 11. Explanation of methods of analysis--continued

Descriptor	Species Determined	Analyst(s)	Equipment Used	Reference(s) or comments	Typical rsd or <i>detection limit</i> (<i>mg/L</i>)
ISOT2	δ ¹⁸ Ο	T.B. Coplen and J.A. Hopple, USGS, Reston, VA (1994 samples) and C. Kendall, USGS, Menlo Park, CA (1995 samples)	DuPont model 21-491 mass spectrometer	Epstein and Mayeda (1953). Standardization against VSMOW ($\delta^{18}O =$ 0 per mil) and SLAP ($\delta^{18}O = -55.5$ per mil)	0.1 per mil
РН	$[\mathrm{H}^+]$	Nordstrom, Ball	Orion Research SA 250 meter, Orion Ross comb. electrode	Two buffer calibration at sample temp. using 9.18, 7.00, 4.01, and 1.68 pH buffers	0.02 pH units
TITR	Alkalinity (as mg/L HCO ₃)	Ball	Orion Research model 960/940 autotitrator, potentiometric detection	Fishman and Friedman (1989)	2% , 0.4
ZGFAAS	Al, Mg	Cunningham	Perkin-Elmer Zeeman 5000 graphite furnace atomic absorption spectrometer, with pyrolytically coated graphite platform cell and Ar purge gas	Analytical wavelength, nanometers:	~5%
				Al - 396.2 Mg - 285.2 Atomization temp.,°C: Al - 2550 Mg - 1700 Char temp., °C: Al - 1500 Mg - 900 Matrix modifier: Al - Mg(NO ₃) ₂ Mg - none	Al: 0.005 Mg: 0.0005

Table 11.	Explanation	of methods	of analysis	continued
10010 11.	Explanation	or memous	or unaryon	continueu

		Combined 1994 Data		Combined 1995 Data					
			Observed	Most probable			Observed	Most probable	
	Analytical	USGS	concentration	value	Analytical	USGS	concentration	value	
Element	method	SRWS	mg/L		method	SRWS	mĮ	mg/L	
Ca	ICP	T117	21.6 [0.5]	20.9 [1.2]	ICP	T117	21.5 [0.5]	20.9 [1.2]	
Mg	ICP	T117	10.3 [0.3]	10.05 [0.44]	ICP	T117	10.9 [0.4]	10.05 [0.44]	
Mg	ZGFAAS	T115	26.6 [1.1]	27.6 [1.0]	ZGFAAS	T117	9.47 [0.48]	10.05 [0.44]	
Na	FAAS	T111	61.2 [1.0]	53.8 [0.5]	ICP	T117	20.8 [0.6]	20.00 [1.26]	
Na	ICP	T117	20.6 [0.6]	20.00 [1.26]	FAAS	T117	18.9 []	20.00 [1.26]	
K	FAAS	T111	2.59 [0.06]	2.67 [0.07]	ICP	T117	<2.65	2.11 [0.19]	
Κ	ICP	T117	2.16 [0.35]	2.11 [0.19]	FAAS	T115	5.24 [0]	5.41 [0.32]	
Κ					FAAS	T117	2.01 [0.02]	2.11 [0.19]	
SO_4					IC	M102	423 [15]	420 [16]	
F					IC	M102	1.1 [0.2]	1.1 [0.1]	
Cl					IC	M102	40 [3]	44 [2]	
Br					IC	M102	< 0.11	0.100 [0.022]	
SiO ₂	ICP	T117	12.6 [0.8]	11.85 [0.64]	ICP	T117	12.7 [0.4]	11.85 [0.64]	
Al	ICP	T117	< 0.35	0.079[0.0194]	ICP	T117	< 0.32	0.0790 [0.0194]	
Al	ZGFAAS	T115	0.028 [0.002]	0.040 [0.020]	ZGFAAS	T117	0.074 [0.002]	0.0790 [0.0194]	
Fe (total)	ICP	T117	0.489 [0.015]	0.474 [0.0182]	ICP	T117	0.497 [0.015]	0.4740 [0.0182]	
В	ICP	T117	0.176 [0.024]	0.151 [0.021]	ICP	T117	0.197 [0.018]	0.151 [0.0208]	
Li	FAAS	T115	0.136 [0.002]	0.132 [0.012]	FAAS	T115	0.126	0.132 [0.012]	
Sr	ICP	T117	0.269 [0.009]	0.265 [0.011]	ICP	T117	0.273 [0.008]	0.265 [0.0111]	
Ba	ICP	T117	0.096 [0.005]	0.0985 [0.0063]	ICP	T117	0.098 [0.005]	0.0985 [0.0063]	
Mn	ICP	T117	0.216 [0.011]	0.220 [0.015]	ICP	T117	0.217 [0.006]	0.220 [0.0149]	
Zn	ICP	T117	0.179 [0.005]	0.176 [0.0093]	ICP	T117	0.182 [0.006]	0.176 [0.0093]	
Pb	ICP	T117	< 0.113	0.005 [0.0013]	ICP	T117	< 0.63	0.0050 [0.0013]	
Be	ICP	T117	0.004 [0.001]	0.0048 [0.0004]	ICP	T117	0.004 [0.001]	0.0048 [0.0004]	
V	ICP	T117	< 0.015	0.0047 [0.0018]	ICP	T117	< 0.013	0.0047 [0.0018]	
Cr	ICP	T117	< 0.068	0.0103 [0.0016]	ICP	T117	< 0.128	0.0103 [0.0016]	
Со	ICP	T117	< 0.030	0.0043 [0.0007]	ICP	T117	< 0.015	0.0043 [0.0007]	
Ni	ICP	T117	< 0.030	0.0100 [0.0025]	ICP	T117	< 0.028	0.0100 [0.0025]	
Cu	ICP	T117	< 0.105	0.0060 [0.0018]	ICP	T117	< 0.122	0.0060 [0.0018]	
Cd	ICP	T117	< 0.030	0.0022 [0.0004]	ICP	T117	< 0.006	0.0022 [0.0004]	
As (total)	ICP	T117	< 0.26	0.0069 [0.0014]	ICP	T117	< 0.22	0.0069 [0.0014]	

Table 12. Measurements of Standard Reference Waters

[Number in brackets represents one sample standard deviation]